

Serial No.: 10/730,992  
Examiner: Shih Chao Chen

**In the claims:**

1-28. (Canceled)

29. (Currently amended) A mounting device comprising:

a radio housing with a radio mounting face including:

a radio nose, and

a locking ring that is rotatably attached to the radio mounting face; and

an antenna housing with an antenna mounting face, including an antenna feed input,

the locking ring being rotatable with respect to the antenna mounting face for being rotated into and out of a secured engagement with the antenna mounting face, with the radio nose being aligned with the antenna feed input, and

the locking ring being attached and held next to the radio mounting face, able to rotate with respect to the radio mounting face, as the locking ring is rotated into and out of the secured engagement with the antenna mounting face.

~~wherein the radio nose is aligned with the antenna feed input, and the locking ring is secured to the antenna mounting face.~~

30. (Previously presented) The mounting device of claim 29, further comprising a plurality of ring tabs attached to the radio mounting face that are displaced from the radio mounting face;

wherein the radio mounting face has a center,

wherein the locking ring is channel-shaped and is positioned adjacent to the radio mounting face, and the channel shaped locking ring has an opening that faces radially toward the center of the radio mounting face, and

wherein the ring tabs extend radially away from the center of the radio mounting face and into the opening to hold the locking ring next to the radio mounting face.

31. (Currently amended) A mounting device comprising:

a radio housing with a radio mounting face including:

132687 (A8690)

Page 3

**BEST AVAILABLE COPY**

Serial No.: 10/730,992  
Examiner: Shih Chao Chen

a radio nose, and  
a locking ring that is rotatably attached to the radio mounting face; and  
an antenna housing with an antenna mounting face, including an antenna feed input,  
wherein:

the radio nose is aligned with the antenna feed input,  
the locking ring is secured to the antenna mounting face.

~~The device of claim 29, wherein the radio mounting face has a center~~ center, and the locking ring rotates about the center and includes a first pinhole at a first radio pinhole position located at a first distance from the radio mounting face center and a second pinhole at a second radio pinhole position located at a second distance from the radio mounting face center, and

the antenna mounting face has a ~~center~~ center, and the locking ring rotates about the center and includes a first pinhole at a first antenna pinhole position located at the first distance from the antenna mounting face center and a second pinhole at a second antenna pinhole position located at the second distance from the antenna mounting face center, and

~~wherein~~ placement of a pin in the first pinholes positions the antenna for a first polarization ~~direction~~ direction, or placement of the pin in the second pinholes positions the antenna for a second polarization direction.

32. (Previously presented) The device of claim 31, wherein the radio mounting face has a circumference and the antenna mounting face has a circumference;

the first radio pinhole is located at a position that is 90 degrees, with respect to the circumference of the radio mounting face, from the second radio pinhole position where the second radio pinhole is located; and the first antenna pinhole and the second antenna pinhole are located at the same circumferential position with respect to the circumference of the antenna mounting face.

33. (Currently amended) A mounting device comprising:  
a radio housing including:

Serial No.: 10/730,992  
Examiner: Shih Chao Chen

a radio mounting face, having a center,  
a plurality of ring tabs attached to the radio mounting face and displaced from the  
radio mounting face,  
a radio nose, and  
a locking ring that is rotatably attached to the radio mounting face,  
wherein the locking ring is channel-shaped and is positioned adjacent to the radio  
mounting face, and the channel shaped locking ring has an opening that faces radially  
toward the center of the radio mounting face, and  
wherein the ring tabs extend radially away from the center of the radio mounting  
face and into the opening to hold the locking ring next to the radio mounting face;  
an antenna housing with an antenna mounting face, including an antenna feed input;  
wherein the radio nose is aligned with the antenna feed input, and the locking ring is  
secured to the antenna mounting face.

~~The device of claim 30, wherein the radio mounting face has a center and the locking ring~~  
~~rotates about the center~~ of the radio mounting face and includes a first pinhole at a first radio  
pinhole position located at a first distance from the radio mounting face center and a second  
pinhole at a second radio pinhole position located at a second distance from the radio mounting  
face center, and

the antenna mounting face has a ~~center-center,~~ and the locking ring rotates about the  
center and includes a first pinhole at a first antenna pinhole position located at the first distance  
from the antenna mounting face center and a second pinhole at a second antenna pinhole position  
located at the second distance from the antenna mounting face center,

wherein placement of a pin in the first pinholes positions the antenna for a first  
polarization ~~direction-direction,~~ or placement of the pin in the second pinholes positions the  
antenna for a second polarization direction.

34. (Previously presented) The device of claim 33, wherein the radio mounting face has a  
circumference and the antenna mounting face has a circumference;

132687 (A8690)

Page 5

**BEST AVAILABLE COPY**

Serial No.: 10/730,992  
Examiner: Shih Chao Chen

the first radio pinhole is located at a position that is 90 degrees, with respect to the circumference of the radio mounting face, from the second radio pinhole position where the second radio pinhole is located; and the first antenna pinhole and the second antenna pinhole are located at the same circumferential position with respect to the circumference of the antenna mounting face.

132687 (A8690)  
Page 6

**BEST AVAILABLE COPY**